

**IN THE CLAIMS**

Please amend the claims to be in the form as follows:

*B*  
*Subcl*

Claim 1 (currently amended): A method of recording marks representing data in a recording medium, said recording medium comprising an information layer having a phase which is reversibly changeable between a crystal phase and an amorphous phase, by irradiating the information layer with a pulsed radiation beam, each mark being written by a sequence of pulses comprising at least one write pulse, the written marks being erasable by irradiating the information layer with a radiation beam having an erase power level (e), a first write pulse of a sequence of pulses being preceded by a cooling pulse having a cooling power level (c) which is lower than the erase power level (e), said radiation beam being generated by a radiation source, characterized in that a last write pulse of a sequence is directly followed by a rear heating pulse having a rear heating power level (r), the rear heating power level (r) being higher than the erase power level (e), and the rear heating power level being a different level from said last write pulse.

Claim 2 (previously presented): A method as claimed in Claim 1, characterized in that the rear heating power level (r) of the rear heating pulse is dependent on properties of the recording medium.

Claim 3 (previously presented): A method as Claimed in Claim 1 for recording marks having lengths of  $nT$ , where T represents the length of one period of a reference clock in a data signal and n represents a predetermined natural number larger than 1, each mark being written by a sequence of (n-1) write pulses, characterized in that the rear heating pulse has a first rear heating power level (r1) when  $n=2$ , a second rear heating power level (r2) when  $n=3$ , and a third rear heating power level (r3) when  $n \geq 4$ , the first rear heating power level (r1), the second rear heating power level (r2), and the third rear heating power level (r3) being dependent on properties of the recording medium.

*B*

B2  
ix  
Cur  
Subcl 7

Claim 4 (previously presented): A method as claimed in Claim 1, characterized in that the first write pulse of a sequence is directly preceded by a front heating pulse having a front heating power level (f), the front heating pulse being directly preceded by the cooling pulse having a cooling power level (c), the front heating power level (f) being higher than the erase power level (e).

Claim 5 (previously presented): A method as claimed in Claim 4, characterized in that the front heating power level (f) of the front heating pulse is dependent on properties of the recording medium.

Claim 6 (previously presented): A method as claimed in Claim 4 for recording marks having lengths of  $nT$ , where  $T$  represents the length of one period of a reference clock in a data signal and  $n$  represents a predetermined natural number larger than 1, each mark being written by a sequence of  $(n-1)$  write pulses, characterized in that the front heating pulse has a first front heating power level (f1) when  $n=2$ , a second front heating power level (f2) when  $n=3$ , and a third front heating power level (f3) when  $n \geq 4$ , the first front heating power level (f1), the second front heating power level (f2), and the third front heating power level (f3) being dependent on properties of the recording medium.

8. Claim X (previously presented): A method as claimed in Claim 1, characterized in that the cooling power level (c) of the cooling pulse is dependent on properties of the radiation source and the recording medium.

7. Claim X (previously presented): A method as claimed in Claim 4 for recording marks having lengths of  $nT$ , where  $T$  represents the length of one period of a reference clock in a data signal and  $n$  represents a predetermined natural number larger than 1, each mark being written by a sequence of  $(n-1)$  write pulses, characterized in that the cooling pulse has a first cooling power level (c1) when  $n=2$ , a second cooling power level (c2) when  $n=3$ , and a third cooling power level (c3) when  $n \geq 4$ , the first cooling power level (c1), the second cooling power level (c2), and the third cooling power level (c3) being dependent on properties of the radiation source and the

B

B2  
Amif  
Subcl  
Conf

recording medium.

Claim 9 (previously presented): A method as claimed in Claim 1, characterized in that the rear heating pulse includes a front portion having the rear heating power level (r), and a rear portion having a power level which is lower than the erase power level (e).

Claim 10 (currently amended): A method of recording marks representing data in a recording medium, said recording medium comprising an information layer having a phase which is reversibly changeable between a crystal phase and an amorphous phase, by irradiating the information layer with a pulsed radiation beam, each mark having a length of  $nT$ , where  $T$  represents the length of one period of a reference clock in a data signal and  $n$  represents a predetermined natural number larger than 1, the marks being written by a sequence of pulses comprising  $(n-1)$  write pulses, the written marks being erasable by irradiating the information layer with a radiation beam having an erase power level (e), a first write pulse of a sequence of pulses being preceded by a cooling pulse having a cooling power level (c) which is lower than the erase power level (e), said radiation beam being generated by a radiation source, characterized in that the cooling pulse has a first cooling power level (c1) when  $n=2$ , a second cooling power level (c2) when  $n=3$ , and a third cooling power level (c3) when  $n \geq 4$ , wherein c1, c2 and c3 are not all the same level and the first cooling power level (c1), the second cooling power level (c2), and the third cooling power level (c3) being dependent on properties the radiation source and of the recording medium.

Claim 11 (currently amended): A method as claimed in Claim 10, characterized in that the first cooling power level (c1) is substantially equal to either the second cooling power level (c2) and or the third cooling power level (c3).

Claim 12 (currently amended): A recording device for recording data in the form of marks on a recording medium, said recording medium comprising an information layer having a phase which is reversibly changeable between a crystal phase and an amorphous phase, by irradiating the information layer with a pulsed radiation beam, the recorded marks being erasable by means of irradiating the information layer with a radiation beam having an erase power level (e), the device comprising a radiation source providing the radiation beam and a control unit for

Serial No. 09/787,094

5

B2  
Can  
Subcl  
cont

controlling the power of the radiation beam, the control unit being operative for providing a sequence of write pulses for writing a mark and controlling the power of the radiation beam such that it has a cooling power level (c) which is lower than the erase power level (e) preceding a first write pulse of a sequence of pulses, characterized in that the control unit is operative for controlling the power of the radiation beam such that it has a rear heating pulse having a rear heating power level (r) directly following a last write pulse of a sequence, the rear heating power level (r) being higher than the erase power level (e) and the rear heating power level being a different level from said last write pulse.

Claim 13 (previously presented): A recording device as claimed in Claim 12, characterized in that the recording device comprises means for determining a value for the rear heating power level (r), which value for the rear heating power level (r) depends on properties of the recording medium.

15. Claim ~~14~~ (previously presented): A recording device as claimed in Claim 12 for recording marks having lengths of  $nT$ , where  $T$  represents the length of one period of a reference clock in a data signal and  $n$  represents a predetermined natural number larger than 1, characterized in that the recording device comprises means for determining a first value for the rear heating power level (r1) when  $n=2$ , a second value for the rear heating power level (r2) when  $n=3$ , and a third value for the rear heating power level (r3) when  $n \geq 4$ , said first value for the rear heating power level (r1), second value for the rear heating power level (r2) and third value for the rear heating power level (r3) being dependent on properties of the recording medium.

16. Claim ~~15~~ (previously presented): A recording device as claimed in Claim 12, characterized in that the control unit is operative for controlling the power of the radiation beam such that it has a front heating pulse having a front heating power level (f) directly preceding a first write pulse and a cooling pulse having a cooling power level (c) directly preceding the front heating pulse, the front heating power level (f) being higher than the erase power level (e) and the cooling power level (c) being lower than the erase power level (e).

B

B2  
Cm  
17.

Claim ~~16~~ (previously presented): A recording device as claimed in Claim 15, characterized in that the recording device comprises means for determining a value for the front heating power level (f), which value for the front heating power level (f) depends on properties of the recording medium.

Subcl  
Cm 19.  
Claim ~~17~~ (previously presented): A recording device as claimed in Claim 15 for recording marks having lengths of  $nT$ , where  $T$  represents the length of one period of a reference clock in a data signal and  $n$  represents a predetermined natural number larger than 1, characterized in that the recording device comprises means for determining a first value for the front heating power level (f1) when  $n=2$ , a second value for the front heating power level (f2) when  $n=3$ , and a third value for the front heating power level (f3) when  $n \geq 4$ , said first value for the front heating power level (f1), second value for the front heating power level (f2) and third value for the front heating power level (f3) being dependent on properties of the recording medium.

20. Claim ~~18~~ (previously presented): A recording device as claimed in Claim 15, characterized in that the recording device comprises means for determining a value for the cooling power level (c), which value for the cooling power level (c) depends on properties of the recording medium.

22. Claim ~~19~~ (previously presented): A recording device as claimed in Claim 15 for recording marks having lengths of  $nT$ , where  $T$  represents the length of one period of a reference clock in a data signal and  $n$  represents a predetermined natural number larger than 1, characterized in that the recording device comprises means for determining a first value for the cooling power level (c1) when  $n=2$ , a second value for the cooling power level (c2) when  $n=3$ , and a third value for the cooling power level (c3) when  $n \geq 4$ , said which first value for the cooling power level (c1), second value for the cooling power level (c2) and third value for the cooling power level (c3) being dependent on properties of the radiation source and the recording medium.

23. Claim ~~20~~ (previously presented): A recording device as claimed in Claim 12, characterized in

B

B2  
Civ  
Subcl  
con 424.

that the control unit is operative for providing the rear heating pulse and controlling the power of the radiation beam such that the rear heating pulse includes a front portion having the rear heating power level (r), and a rear portion having a power level which is lower than the erase power level (e).

Claim ~~24~~ (currently amended): A recording device for recording data in the form of marks on a recording medium, said recording medium comprising an information layer having a phase which is reversibly changeable between a crystal phase and an amorphous phase, and said marks having lengths of  $nT$ , where  $T$  represents the length of one period of a reference clock in a data signal and  $n$  represents a predetermined natural number larger than 1, by irradiating the information layer by a pulsed radiation beam, the recorded marks being erasable by irradiating the information layer with a radiation beam having an erase power level (e), the device comprising a radiation source providing the radiation beam and a control unit for controlling the power of the radiation beam, the control unit being operative for providing a sequence of write pulses for writing a mark and controlling the power of the radiation beam such that it has cooling power level (c) which is lower than the erase power level (e) preceding a first write pulse of a sequence of pulses, characterized in that the recording device comprises means for determining a first value for the cooling power level (c1) when  $n=2$ , a second value for the cooling power level (c2) when  $n=3$ , and a third value for the cooling power level (c3) when  $n \geq 4$ , said first value for the cooling power level (c1), second value for the cooling power level (c2) and third value for the cooling power level (c3) being dependent on properties of the radiation source and the recording medium, wherein c1, c2 and c3 are not all the same level.

25. Claim ~~25~~ (currently amended): A recording device as claimed in Claim 21, characterized in that the first value for the cooling power level (c1) is substantially equal to either the second value for the cooling power level (c2) ~~and~~ or the third value for the cooling power level (c3).

14. Claim ~~24~~ (currently amended): ~~A recording medium for use in a recording device as claimed in Claim 13, said recording medium comprising said an information layer having said a phase which is reversibly changeable between said a crystal phase and said an amorphous phase, and said recording medium further comprising an area containing recording parameters,~~

B

62  
Crit  
Subcl  
Cur 4

characterized in that the area containing recording parameters comprises a value for the rear heating power level (r).

18. Claim ~~24~~ (currently amended): A ~~recording medium for use in a recording device as claimed in~~ Claim 16, said recording medium comprising said an information layer having said -a- phase which is reversibly changeable between said -a crystal phase and said an amorphous phase, and said recording medium further comprising an area containing recording parameters, characterized in that the area containing recording parameters comprises a value for the front heating power level (f).

21. Claim ~~25~~ (currently amended): A ~~recording medium for use in a recording device as claimed in~~ Claim 18, said recording medium comprising said an information layer having said -a- phase which is reversibly changeable between said -a crystal phase and said an amorphous phase, and said recording medium further comprising an area containing recording parameters, characterized in that the area containing recording parameters comprises a value for the cooling power level (c).

Claim 26 (new): A recording medium for use in a recording device, said recording medium comprising an information layer having a phase which is reversibly changeable between a crystal phase and an amorphous phase by irradiating the information layer with a pulsed radiation beam to create a series of recorded marks that are erasable by irradiating the information layer with pulsed radiation having an erase power level (e), and wherein said information layer further comprises an area containing recording parameters.

Claim 27 (new): The recording medium of Claim 26 wherein said area containing recording parameters further comprises a rear heating power level (r) parameter.

Claim 28 (new): The recording medium of Claim 26 wherein said area containing recording parameters further comprises a front heating power level (f) parameter.

Claim 29 (new): The recording medium of Claim 26 wherein said area containing recording

B

Subcl  
B2  
Cond.

parameters further comprises a cooling power level (c) parameter.

B